

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: OVERCOAT 2020 MARINE BLUE
 P PRODUCT CODE: 14-2020-XX
 1 G

HMIS CODES H F R
 1 4

SECTION 1 - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: BURKE INDUSTRIAL COATINGS
 ADDRESS: 600 S. 74th Place, Suite 108, Ridgefield, WA 98642
 EMERGENCY PHONE: 800) 255-3924 INFORMATION PHONE: (360)887-8819
 CHEM-TEL)
 TRADE NAME: OVERCOAT 2020
 PRODUCT CLASS: AEROSOL - CHAIN STOPPED ALKYD RESIN
 MANUFACTURERS CODE IDENTIFICATION: BW-2020-0000
 EFFECTIVE DATE: 1-5-10 NAME OF PREPARER: DARRELL BADERTSCHER

SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENT -(CAS#)	PERCENT	ACGIH TLV (TWA)/OSHA PEL		VAPOR PRESSURE AEROSOL CANS	
		PPM	MG/M3	40 P.S.I.A. @ 70 DEG. F.	LEL
ALUMINUM POWDER (NL) (1) (7429-90-5)	1.51	ND	10.00	ND	
PHTHALOCYANINE BLUE (1) (147-14-8)	.54	ND	10.00	ND	
XYLENE (1) (1330-20-7)	10.16	ND	435.00		
ETHYL BENZENE (1) (100-41-4)	2.55	100.00	434.00	1.20	
TOLUENE (1) (2) (108-88-3)	9.44	100.00	377.00	1.27	
ACETONE (1) (67-64-1)	28.27	750.00	1,780.00	2.60	
MINERAL SPIRITS (64742-47-8)	.92	100.00	525.00		
VARNISH MAKERS & PAINTER NAPHTHA (8032-32-4)	.21	300.00	1,370.00	1.10	
ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9)	(1)	1.31	ND	ND	1.26
SC0100 SOLVENT (64742-95-6)	.91	50.00	245.00	1.00	
PROPANE - (74-98-6)	15.0	ND	ND	2.30	
ISOBUTANE - (75-28-5)	10.0	ND	ND	1.90	

MATERIAL	8-HOUR TIME WEIGHTED AVERAGE	ACCEPTABLE CEILING CONCENTRATION	ACCEPTABLE MAXIMUM PEAK ABOVE THE ACCEPTANCE CEILING CONCENTRATION FOR AN 8-HOUR SHIFT
TOLUENE	200 PPM	300 PPM	CONCENTRATION 500 PPM MAXIMUM DURATION 10 MINUTES

- (1) THIS CHEMICAL IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III
- (2) THIS CHEMICAL IS ON THE LIST OF "CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER REPRODUCTIVE TOXICITY" (PROPOSITION 65)

SECTION 3 - PHYSICAL/DATA

BOILING POINT: N/A
EVAPORATION RATE: FASTER THAN ETHER.
VAPOR DENSITY: HEAVIER THAN AIR
PERCENT VOLATILE ORGANIC BY WEIGHT: 79.0%
WEIGHT PER GALLON: 6.580

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: AEROSOL-10 DEG. F (T.O.C.) LEL: SEE SECTION 2
FLAMMABILITY CLASSIFICATION: 1A
OSHA: CLASS 1A FLASH POINT BELOW 73 F. AND A BOILING POINT BELOW 100 F.
DOT: CONSUMER COMMODITY ORMD

EXTINGUISHING MEDIA: USE CARBON DIOXIDE, DRY CHEMICAL OR FOAM.

UNUSUAL FIRE AND EXPLOSION HAZARDS

EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

SPECIAL FIRE FIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT BURSTING. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WEAR GOGGLES AND SELF CONTAINED BREATHING APPARATUS.

SECTION 5 - HEALTH HAZARD

THRESHOLD LIMIT VALUE: SEE SECTION 2

ACUTE OVEREXPOSURE/FIRST AID:

INHALATION: EXPOSURE TO SOLVENT VAPORS CONCENTRATION EXCEEDING THE ESTABLISHED THRESHOLD LIMIT VALUES CAN CAUSE RESPIRATORY SYSTEM IRRITATION. SYMPTOMS OF OVEREXPOSURE ARE IRRITATION, HEADACHE, DIZZINESS, NAUSEA, POSSIBLE UNCONSCIOUSNESS AND ASPHYXIATION.

FIRST AID: REMOVE PATIENT TO FRESH AIR. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION, SEEK IMMEDIATE MEDICAL ATTENTION.

EYE CONTACT: MAY CAUSE EYE IRRITATION ESPECIALLY UPON DIRECT CONTACT WITH THE SPRAY.

FIRST AID: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

SKIN CONTACT: PROLONGED OR REPEATED LIQUID CONTACT MAY CAUSE DEFATTING OF THE SKIN, LEADING TO IRRITATION AND DERMATITIS.

FIRST AID: WASH WITH SOAP AND WATER.

INGESTION: ACCIDENTAL INGESTION IS UNLIKELY FROM AN AEROSOL CAN. IF INGESTED CALL A PHYSICIAN IMMEDIATELY.

FIRST AID: CALL A PHYSICIAN IMMEDIATELY.

CHRONIC OVEREXPOSURE:

ALUMINUM POWDER (NL) (1)
(7429-90-5)
OVEREXPOSURE - NONE CURRENTLY KNOWN.

PRODUCT CODE:14-2020-XX
5

MATERIAL SAFETY DATA SHEET

PAGE 3 OF

PHTHALOCYANINE BLUE (1)
(147-14-8)

OVEREXPOSURE - NONE KNOWN. CONTAINS COPPER COMPOUNDS - 24% BY WEIGHT. AS COPPER - 12% BY WEIGHT.

XYLENE (1)
(1330-20-7)

OVEREXPOSURE - HEALTH STUDIES HAVE SHOWN THAT MANY PETROLEUM HYDROCARBONS POSE POTENTIAL HUMAN HEALTH RISK WHICH MAY VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS, OR FUMES SHOULD BE MINIMIZED. REPORTS OF ANIMAL TEST STUDIES HAVE SHOWN POSSIBLE EFFECTS TO: THE LIVER, KIDNEYS, AND THE LUNGS. REPORTS OF ANIMAL TEST STUDIES HAVE SHOWN EMBRYO/FETOXIC EFFECTS. THE RELEVANCE OF THESE EFFECTS TO MAN IS UNKNOWN. HIGH VAPOR CONCENTRATIONS (GREATER THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT, MAY CAUSE HEADACHES AND DIZZINESS, ARE ANESTHETIC AND MAY HAVE OTHER NERVOUS SYSTEM EFFECTS INCLUDING DEATH.

ETHYL BENZENE (1)
(100-41-4)

OVEREXPOSURE - MAY CAUSE SEVERE EYE IRRITATION, REDNESS, TEARING, AND BLURRED VISION, PROLONGED OR REPEATED EXPOSURE CAN CAUSE IRRITATION, DEFATTING AND DEMITITIS. EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, CENTRAL NERVOUS SYSTEM EFFECTS INCLUDE DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS, AND EVEN DEATH. CAN CAUSE GASTRO-INTESTINAL IRRITATION, VOMITING, AND DIARRHEA, ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONTIS WHICH CAN BE FATAL.

TOLUENE (1) (2)
(108-88-3)

OVEREXPOSURE - WHILE THERE IS NO EVIDENCE THAT INDUSTRIAL ACCEPTABLE LEVELS OF TOLUENE (E.G. THE TLV) HAVE PRODUCED CARDIAC EFFECTS IN HUMANS, ANIMAL STUDIES HAVE SHOWN THAT INHALATION OF HIGH LEVELS OF TOLUENE PRODUCED CARDIAC SENSITIZATION. SUCH SENSITIZATION MAY CAUSE FATAL CHANGES IN HEART RHYTHMS. THIS LATTER EFFECT WAS SHOWN TO BE ENHANCED BY HYPOXIA OR THE INJECTION OF ADRENALIN-LIKE AGENTS. RATS EXPOSED TO 1400 PPM OR 1200 PPM OF TOLUENE FOR 14H/DAY FOR 4 OR 5 WEEKS (RESPECTIVELY) EXHIBITED HIGH FREQUENCY HEARING DEFICITS. THE SIGNIFICANCE OF THIS INFORMATION TO MAN IS UNKNOWN.

ACETONE (1)
(67-64-1)

OVEREXPOSURE - HIGH VAPOR CONCENTRATIONS MAY IRRITATE THE EYES AND MUCOUS MEMBRANES OF THE NOSE AND THROAT. SEVERE OVEREXPOSURE (I.E. -12,000 PPM) CAN CAUSE CNS DEPRESSION INCLUDING NAUSEA, VOMITING, HEADACHES, INCOORDINATION AND DIZZINESS. REPEATED OR PROLONGED CONTACT OF THE LIQUID WITH THE SKIN CAN CAUSE REDNESS AND A DRY, SCALY AND FISSURED DERMATITIS. EYE CONTACT RESULTING FROM SPLASHES OR HIGH VAPOR CONCENTRATION EXPOSURE IS IRRITATING. WHEN ACETONE WAS ABSORBED SYSTEMICALLY, IT CAUSED CATARACTS IN LABORATORY ANIMALS. WHEN INGESTED THE EFFECTS ARE INTOXICATING. THESE ACUTE SYMPTOMS MIGHT INCLUDE EARLY EMOTIONAL INSTABILITY, IMPAIRED MOTOR COORDINATION, NAUSEA, VOMITING, DROWSINESS, STUPER AND FINALLY COMA. 10 TO 20 ML HAS BEEN TAKEN ORALLY WITHOUT ILL EFFECTS.

MINERAL SPIRITS
(64742-47-8)

OVEREXPOSURE - NARCOSIS IN HIGH CONCENTRATION. MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.

VARNISH MAKERS & PAINTER
NAPHTHA (8032-32-4)

OVEREXPOSURE - MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. CENTRAL NERVOUS SYSTEM DEPRESSION IN HIGH CONCENTRATIONS.

ETHYLENE GLYCOL MONOPROPYL (1)
ETHER (2807-30-9)

OVEREXPOSURE - EXPOSURE OF EXPERIMENTAL ANIMALS VIA INHALATION, SKIN CONTACT, OR INGESTION PRODUCES A TOXIC EFFECT ON THE RED BLOOD CELL. IN STUDIES OF THE RELATED CHEMICAL, 2-BUTOXYETHANOL, RATS WERE AT LEAST THREE (3) TIMES MORE SENSITIVE THAN HUMANS TO THIS TOXIC EFFECT.

SECTION 6 - REACTIVITY DATA

SC-100 SOLVENT
(64742-95-6)

OVEREXPOSURE - HEALTH STUDIES HAVE SHOWN THAT MANY PETROLEUM HYDROCARBONS POSE POTENTIAL HUMAN RISKS WHICH MAY VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MIST OR FUMES SHOULD BE MINIMIZED. HIGH VAPOR CONCENTRATIONS (GREATER THAN APPROXIMATELY 1,000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT, MAY CAUSE HEADACHES AND DIZZINESS, ARE ANEATHETIC, AND MAY HAVE OTHER CENTRAL NERVOUS EFFECTS INCLUDING DEATH. THIS PRODUCT CAN BE DEFINED AS: LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM). IT CONSISTS PREDOMINATELY OF C8-C10 AROMATIC HYDROCARBONS, PRIMARILY C9

STABILITY: STABLE

CONDITIONS TO AVOID: DO NOT STORE ABOVE 120 DEG. F. KEEP FROM SPARKS, PILOT LIGHTS OR OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN

HAZARDOUS DECOMPOSITION PRODUCTS: MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON DIOXIDE AND/OR CARBON MONOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: N/A

SECTION 7 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING VAPORS, VENTILATE AREA. WIPE UP WITH INERT MATERIALS AND PLACE IN APPROPRIATE CONTAINER.

WASTE DISPOSAL METHODS: DO NOT INCINERATE AEROSOL, DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT PLACE AEROSOL CANS IN HOME COMPACTOR. DO NOT PUNCTURE.

SECTION 8 - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: AVOID CONTINUOUS BREATHING OF VAPORS AND SPRAY MIST. A SELF CONTAINED BREATHING APPARATUS REQUIRED FOR CONCENTRATIONS ABOVE TLV LIMITS.

VENTILATION: USE WITH ADEQUATE VENTILATION, SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS.

PROTECTIVE GLOVES: OPTIONAL

EYE PROTECTION: ONLY UNDER CONDITIONS WHERE SPRAY MIST MIGHT GET INTO EYES.

SECTION 9 - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT STORE ABOVE 120 DEG. F. EXPOSURE TO HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING.

OTHER PRECAUTIONS: USE ONLY AS DIRECTED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

PERIODICALLY USER SHOULD REQUEST NEW MSDS TO ASSURE IT MATCHES CURRENT FORMULATION. THIS MSDS IS BASED ON FORMULA #BW-2020-0000.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE BY BURKE INDUSTRIAL COATINGS. IT IS TRUE AND ACCURATE TO THE BEST OF OUR KNOWLEDGE, BUT IS NOT INTENDED TO BE ALL INCLUSIVE. USERS SHOULD CONSIDER THIS INFORMATION AS A SUPPLEMENT TO OTHER INFORMATION GATHERED BY THEM AND MUST MAKE THEIR OWN DETERMINATION OF SUITABILITY AND COMPLETENESS TO ASSURE PROPER SAFE USE AND DISPOSAL OF THESE MATERIALS.

ABBREVIATIONS:

N/D	NO DATA
N/A	NOT APPLICABLE
ACGIH (TLV)	AMERICAN CONFERENCE OF GOVERNMENT INDUSTRIAL HYGIENISTS. (THRESHOLD LIMIT VALUE)
PEL	PERMISSIBLE EXPOSURE LIMITS
PPM	PARTS PER MILLION
MGM3	MILLIGRAMS PER CUBIC METER
CAS #	CHEMICAL ABSTRACT SERVICE NUMBER
PSIA	POUNDS PER SQUARE INCH - ABSOLUTE
F.	DEGREES FAHRENHEIT
TOC	TAG OPEN CUP
(A-1)	CONFIRMED HUMAN CARCINOGEN BY NTP, IARC, AND/OR OSHA
(A-2)	SUSPECTED HUMAN CARCINOGEN BY NTP, IARC, AND/OR OSHA

SECTION 10 - DISCLAIMER

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with Burke Industrial Coatings or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. To our knowledge, this MSDS complies with 29 CFR 1910.1200